


ALLOY/STRUCTURAL — MACHINE SCREWS

NAS600 - NAS603 MACHINE SCREWS



Thread	Length	Part No.	Price Ea.
4-40	.188	NAS600-3P	\$0.11
	.250	NAS600-4P	\$0.06
	.312	NAS600-5P	\$0.09
	.375	NAS600-6P	\$0.09
	.438	NAS600-7P	\$0.08
	.500	NAS600-8P	\$0.07
6-32	.188	NAS601-3P	\$0.12
	.250	NAS601-4P	\$0.07
	.312	NAS601-5P	\$0.08
	.375	NAS601-6P	\$0.09
	.438	NAS601-7P	\$0.08
	.500	NAS601-8P	\$0.09
	.562	NAS601-9P	\$0.09
	.625	NAS601-10P	\$0.10
	.750	NAS601-12P	\$0.14
	.188	NAS602-3P	\$0.15
8-32	.250	NAS602-4P	\$0.11
	.312	NAS602-5P	\$0.11
	.375	NAS602-6P	\$0.14
	.438	NAS602-7P	\$0.11
	.500	NAS602-8P	\$0.15
	.562	NAS602-9P	\$0.14
	.625	NAS602-10P	\$0.12
	.688	NAS602-11P	\$0.13
	.750	NAS602-12P	\$0.13
	.813	NAS602-13P	\$0.14
	.875	NAS602-14P	\$0.15
	1.00	NAS602-16P	\$0.15
	.250	NAS603-4P	\$0.17
	10-32	.312	NAS603-5P
.375		NAS603-6P	\$0.14
.438		NAS603-7P	\$0.18
.500		NAS603-8P	\$0.14
.562		NAS603-9P	\$0.21
.625		NAS603-10P	\$0.16
.688		NAS603-11P	\$0.19
.750		NAS603-12P	\$0.18
.813		NAS603-13P	\$0.17
.875		NAS603-14P	\$0.28
.938		NAS603-15P	\$0.16
1.00		NAS603-16P	\$0.21
1.125		NAS603-18P	\$0.23
1.25		NAS603-20P	\$0.39

- Phillips Pan Head
- Alloy Steel (8740)
- Finish - Cadmium per QQ-P-416
- Tensile -160,000 - 180,000 PSI




HA

NAS1096 HEX HEAD SCREWS



Thread	Length	Part No.	Price Ea.
6-32	.375	NAS1096-1-6	\$0.14
	.438	NAS1096-1-7	\$0.11
	.500	NAS1096-1-8	\$0.19
	.562	NAS1096-1-9	\$0.16
	.625	NAS1096-1-10	\$0.15
	.750	NAS1096-1-12	\$0.18
8-32	.312	NAS1096-2-5	\$0.10
	.375	NAS1096-2-6	\$0.13
	.438	NAS1096-2-7	\$0.13
	.500	NAS1096-2-8	\$0.13
	.562	NAS1096-2-9	\$0.18
	.625	NAS1096-2-10	\$0.17
	.750	NAS1096-2-12	\$0.17
	.312	NAS1096-3-5	\$0.09
10-32	.375	NAS1096-3-6	\$0.18
	.438	NAS1096-3-7	\$0.18
	.500	NAS1096-3-8	\$0.17
	.562	NAS1096-3-9	\$0.16
	.625	NAS1096-3-10	\$0.18
	.750	NAS1096-3-12	\$0.23
	.875	NAS1096-3-14	\$0.26
	1.00	NAS1096-3-16	\$0.28
	1.25	NAS1096-3-20	\$0.23




- Phillips Hex Head
- Alloy Steel per MIL-S-6049
- Finish - Cadmium per QQ-P-416 Type II
- Tensile - 125,000-145,000 PSI

NAS1801 HEX HEAD SCREWS



Thread	Length	Part No.	Price Ea.
8-32	.250	NAS1801-08-4	\$0.15
	.312	NAS1801-08-5	\$0.17
	.375	NAS1801-08-6	\$0.16
	.438	NAS1801-08-7	\$0.14
	.500	NAS1801-08-8	\$0.19
	.562	NAS1801-08-9	\$0.22
	.625	NAS1801-08-10	\$0.18
	.750	NAS1801-08-12	\$0.22
	.875	NAS1801-08-14	\$0.22
	1.00	NAS1801-08-16	\$0.21
	1.125	NAS1801-08-18	\$0.21
	1.25	NAS1801-08-20	\$0.21
	1.375	NAS1801-08-22	\$0.45
	10-32	.312	NAS1801-3-5
.375		NAS1801-3-6	\$0.19
.438		NAS1801-3-7	\$0.19
.500		NAS1801-3-8	\$0.21
.562		NAS1801-3-9	\$0.26
.625		NAS1801-3-10	\$0.24
.750		NAS1801-3-12	\$0.26
.875		NAS1801-3-14	\$0.24
1.00		NAS1801-3-16	\$0.34
1.125		NAS1801-3-18	\$0.27
1.25		NAS1801-3-20	\$0.28
1.375		NAS1801-3-22	\$0.48
1.50		NAS1801-3-24	\$0.51




- Phillips Hex Head
- Alloy Steel Per MIL-S-6049
- Finish - Cad Plate per QQ-P-416, Type II
- Tensile - 160,000-185,000 PSI

NAS1202 / NAS1203 FLUSH HEAD SCREWS

- Phillips 100° Flat Head
- Tensile - 160,000 - 180,000 PSI
- Alloy Steel Per MIL-S-6049
- Finish - Cadmium per QQ-P-416, Type II



Thrd.	Grip	Lgth.	Part No.	Price Ea.
8-32	.125	.401	NAS1202-2	\$0.12
	.188	.464	NAS1202-3	\$0.16
	.250	.526	NAS1202-4	\$0.13
	.312	.588	NAS1202-5	\$0.13
	.375	.651	NAS1202-6	\$0.14
	.438	.714	NAS1202-7	\$0.15
10-32	.125	.401	NAS1203-2	\$0.15
	.188	.464	NAS1203-3	\$0.14
	.250	.526	NAS1203-4	\$0.15
	.312	.588	NAS1203-5	\$0.17
	.375	.651	NAS1203-6	\$0.18
	.438	.714	NAS1203-7	\$0.15
	.500	.776	NAS1203-8	\$0.18




MS5199 MACHINE SCREWS

- Phillips 82° Flat Head
- Stainless Steel

Thrd.	Lgth.	Part No.	Each	Thrd.	Lgth.	Part No.	Each
2-56	.188	MS51959-2	\$0.04	6-32	.312	MS51959-27	\$0.07
	.250	MS51959-3	\$0.04		.375	MS51959-28	\$0.07
	.312	MS51959-4	\$0.04		.438	MS51959-29	\$0.07
	.375	MS51959-5	\$0.04		.500	MS51959-30	\$0.07
	.250	MS51959-13	\$0.04		.625	MS51959-31	\$0.07
4-40	.312	MS51959-14	\$0.05	8-32	.375	MS51959-43	\$0.09
	.375	MS51959-15	\$0.05		.438	MS51959-44	\$0.09
	.438	MS51959-16	\$0.07		.500	MS51959-45	\$0.09
	.500	MS51959-17	\$0.06		.625	MS51959-46	\$0.09
					.750	MS51959-47	\$0.11

NAS623 PAN HEAD SCREWS

- Phillips Pan Head
- Alloy Steel per MIL-S-6049
- Finish: Cadmium per QQ-P-416, Type II
- Tensile: 160,000-180,000 PSI



Thrd.	Lgth.	Part No.	Each	Thrd.	Lgth.	Part No.	Each
8-32	.338	NAS623-2-1	\$0.14	10-32	.588	NAS623-3-5	\$0.17
	.401	NAS623-2-2	\$0.15		.651	NAS623-3-6	\$0.18
	.464	NAS623-2-3	\$0.16		.714	NAS623-3-7	\$0.22
	.526	NAS623-2-4	\$0.14		.776	NAS623-3-8	\$0.19
	.588	NAS623-2-5	\$0.19		.838	NAS623-3-9	\$0.22
	.651	NAS623-2-6	\$0.21		.901	NAS623-3-10	\$0.17
	.714	NAS623-2-7	\$0.19		.964	NAS623-3-11	\$0.19
	.776	NAS623-2-8	\$0.21		1.026	NAS623-3-12	\$0.21
	.838	NAS623-2-9	\$0.20		1.088	NAS623-3-13	\$0.18
	.901	NAS623-2-10	\$0.17		1.151	NAS623-3-14	\$0.21
	.964	NAS623-2-11	\$0.21		1.214	NAS623-3-15	\$0.24
	1.026	NAS623-2-12	\$0.20		1.276	NAS623-3-16	\$0.21
	.401	NAS623-3-2	\$0.16		1.338	NAS623-3-17	\$0.24
	.464	NAS623-3-3	\$0.18		1.401	NAS623-3-18	\$0.32
.526	NAS623-3-4	\$0.15					